



## POND & WATER FEATURE PUMPS 240V

### RP SERIES

Economical, quiet running, centrifugal pumps with generous cable lengths. These pumps have numerous applications for aquarium, garden fountains, table and wall fountains and hydroponics.

CODE	PUMP MODEL	CABLE LENGTH	DRY-MOUNT FLOODED	DIMENSIONS (mm)			INLET	OUTLET	WATTS	MAX FLOW (L/Hr)	MAX HD (m)
				LENGTH	WIDTH	HEIGHT					
9017	RP260	5m	NO	60	45	60		10mm push fit	5.5	260	0.45
9031	RP550	5m	NO	75	50	70		8-10-12mm push fit	10	550	1.22
9062	RP610	10m	YES	120	60	85	½" BSP	¾" BSP	11	610	1.2
9192	RP900	10m	YES	120	60	85	½" BSP	½" BSP	19	900	1.9
9093	RP1100	10m	YES	130	90	105	½" BSP	½" BSP	17	1100	2.0
9123	RP1500	10m	YES	130	90	110	½" BSP	½" BSP	20	1500	2.0
9154	RP2400	10m	YES	155	100	120	1" BSP	½" BSP	40	2300	2.4
9178	RP3500	10m	YES	170	120	150	1" BSP	¾" BSP	60	3500	2.4
9185	RP4000	10m	YES	170	120	150	1" BSP	¾" BSP	70	4000	2.75

#### APPLICATIONS

- Water Features
- Garden Ponds
- Indoor Fountains
- Urns and Amphoras
- Table Fountains
- Hydroponics
- Statues

#### FEATURES

- Proven Performance
- Fresh or Salt Water
- Fully Submersible
- Quiet, Continuous Operation
- Built in Flow Control
- Spare Parts Available
- Electrical Safety Approval to AS/NZS 60335.2.41
- Kit does not include fountain nozzles



Head (m)	Approximate Flow Rate in Litres per Hour (Without Restriction)								
2.75									(0@2.75m)
2.5							(0@2.4m)	(0@2.4m)	400
2.25							300	300	1000
2.0					(0@ 2.0m)	(0@ 2.0m)	600	600	1300
1.75				(0@1.9m)	200	250	850	1000	1650
1.5				200	400	500	1150	1500	2000
1.25		(0@ 1.2m)	(0@ 1.2m)	300	650	700	1350	2000	2400
1.0		40	100	475	700	850	1600	2500	2700
0.75		170	220	550	825	1000	1750	3000	3000
0.5	(0@0.45m)	400	450	675	950	1200	2000	3150	3400
0.25	150	480	525	800	1075	1350	2200	3300	3600
0.0	260	550	610	850	1100	1500	2300	3500	4000
<b>MODEL</b>	<b>RP260</b>	<b>RP550</b>	<b>RP610</b>	<b>RP900</b>	<b>RP1100</b>	<b>RP1500</b>	<b>RP2400</b>	<b>RP3500</b>	<b>RP4000</b>