

POND & WATER FEATURE PUMPS LOW VOLTAGE

RPLV SERIES



Economical quiet running, centrifugal pumps in safe, low voltage, with generous 10m cable lengths (except RP550LV) and outdoor transformers. These pumps have numerous applications for aquariums, garden fountains, table and wall fountains and hydroponics. All are saltwater compatible and are fitted with flow control and prefilter foam (except RP550LV)

CODE	PUMP MODEL	CABLE LENGTH	DRY-MOUNT FLOODED	DIMENSIONS (mm)			INLET	OUTLET	WATTS	MAX FLOW (L/Hr)	MAX HD (m)
				Length	Width	Height					
9604	RP550LV 12 Volt AC	5m	NO	75	50	70		8-10-12mm push fit	10	550	1.22
9659	RP850LV 24 Volt AC	10m	YES	120	90	85	½" BSP	½" BSP	19	850	1.8
9673	RP1100LV 24 Volt AC	10m	YES	130	90	105	½" BSP	½" BSP	17	1100	2.0
9697	RP1500LV 24 Volt AC	10m	YES	130	90	110	½" BSP	½" BSP	20	1500	2.0
9727	RP2400LV 24 Volt AC	10m	YES	155	100	120	1" BSP	½" BSP	40	2300	2.4
9758	RP4000LV 24 Volt AC	10m	YES	170	120	150	1" BSP	¾" BSP	70	4000	2.75
9901	Low Voltage Extension Lead	10m	-	-	-	-	-	-	12V- 24V	-	-

APPLICATIONS

- Water Features
- Garden Ponds
- Indoor Fountains
- Urns and Amphoras
- Table Fountains
- Hydroponics
- Statues

FEATURES

- Proven Performance
- Fresh or Salt Water
- Fully Submersible
- Quiet, Continuous Operation
- Built in Flow Control
- Low Voltage Outdoor Transformer with 10m cable (except RP550LV - 5m cable)
- Electrical Safety Approval
- Kit does not include fountain nozzles



Head (m)	Approximate Flow Rate in Litres per Hour (Without Restriction)					
2.75						(0 @ 2.75m)
2.5					(0 @ 2.4m)	400
2.25					300	1000
2.0			(0 @ 2.0m)	(0 @ 2.0m)	600	1300
1.75		(0@1.8m)	200	250	850	1650
1.5		200	400	500	1150	2000
1.25	(0 @ 1.2m)	300	650	700	1350	2400
1.0	40	475	700	850	1600	2700
0.75	170	550	825	1000	1750	3000
0.50	400	675	950	1200	2000	3400
0.25	480	800	1075	1350	2200	3600
0.0	550	850	1100	1500	2300	4000
MODEL	RP550LV	RP850LV	RP1100LV	RP1500LV	RP2400LV	RP4000LV